

PRODUCT FICHE

Supplier's name	VALLOX OY
Product model name	Vallox 245 MV enthalpy
Cell	Enthalpy
SEC cold climate	-80.779 kWh/m ² a
SEC average climate	-42.634 kWh/m ² a
SEC warm climate	-18.156 kWh/m ² a
SEC-class cold climate	A+
SEC-class average climate	A+
SEC-class warm climate	E
General topology EcoDesign	Bidirectional
Motor und Antrieb EcoDesign	Variable speed
Type of heat recovery system	Recuperative
Temperature efficiency of heat recovery	83 %
Maximum supply airflow EcoDesign	915 m ³ /h
Input power of fans at maximum airflow (W)	324 W
Sound power level	45 dB (L _{WA})
Reference airflow rate	0.1800 m ³ /s
Reference pressure difference	50 Pa
Specific power input (SPI)	0.1830
Ventilation control EcoDesign	Local demand control
Specified maximum internal leak of the enclosure	2.0 %
Specified maximum external leak of the enclosure	2.0 %
Filter replacement	"Change filter!" text will appear on the control panel screen. Regular filter replacement is very important for the unit's faultless performance and energy efficiency.
Demolition and removal instructions	www.vallox.com
AEC cold climate	678.9 kWh/a
AEC average climate	141.9 kWh/a
AEC warm climate	96.9 kWh/a
AHS cold climate	8902.0 kWh
AHS average climate	4550.5 kWh
AHS warm climate	2057.7 kWh